



CaviBlaster 1325-G CaviMax

Gasoline Engine, 13 gpm & 2,500 psi

Specifications and Options

Our most popular commercial unit, is a compact and lightweight system with superior cleaning performance utilizing the Ultra-Cavitation technology

Accessories Included:

Feed Hose (15 feet) with electric suction pump, By-Pass Hose (15 feet), High Pressure Hose (50 feet), Zero-Thrust Balanced Gun, Battery Start

Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections
Max. Pressure hose length recommended up to 300 ft (100 meters) total

SKID Dimensions	
Height	29" / 74 cm
Width	26" / 66 cm
Length (w/o handle)	35" / 89 cm
Length (w handle)	45" / 115 cm
Weight	265 Lbs / 120 Kg

Pump System	
Pressure Pump	AR XWLSS 50.15 N
Pump Type	Triplex plunger – Marine Brass
Flow Rate	13.2 gpm / 50 L/m
Nozzle Pressure	2,500 psi / 173 Bar
Hose Diam. - Max. Lgth	1/2" - 300 LF / 100m
Hose Ends / QC / QD	Stainless Steel
Regulating Unloader	VB 80/280 Stainless Steel
Plumbing / Fittings	Stainless Steel
Filter / Strainer	PVC w/Stainless Steel Screen

Drive System	
Engine	Honda GX800
Engine Type	2-cylinder air-cooled
Intake System	Naturally aspirated
Combustion System	Electronic Fuel Injection
Power Output Max	28 HP / 20.9 kW @ 3,600rpm
Clutch Type	Belt Drive
Starting System	Electric
Safety system	Low/Hot oil alarm sensor

Feed System	
Feed Pump	Johnson Pump Mod L2200
Type	Submersible Bilge
Shaft	Stainless Steel
Flow/Rate @ Max Lift	31 gpm @ 3' / 1 m
Power requirement	12V @ 7.5 Amp

Shipping Dimensions	
Pallet 40x48x36"	330 Lbs Gross weight

Ideal For
Small to Mid size Boat Hulls
Piers, Pilings & Seawalls
Running gear & Out drivers
Pools & Indoor Underwater Installations

Tool Options
Zero-Thrust Balanced Gun
Double Un-Balanced Guns
Single CaviDome
ROV Lance

* Pricing and specifications subject to change without notice

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA
Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com



CAVIBLASTER™