

UB01 Non-Balanced Diver Gun

Specifications and Options

This cutting-edge industrial innovation represents a formidable solution for the meticulous task of thorough cleaning It excels in efficiently removing various forms of marine fouling, while preserving the integrity of protective coatings. This versatile diver gun can be precisely configured to accommodate a spectrum of operational requirements, offering tailored thrust configurations such as 50-50 thrust ratios.

Each CaviBlaster Gun / Lance is meticulously designed with an internal configuration that is unique unto the unit it is paired with.

	Configurable to		Gun Dimensions	
	0625-G	0520-G	Stainless Steel	Material
			0.126" (Schedule 80)	Wall Thickness
			7/8" / 2.22 cm	Diameter
			10 1/2" / 26.7 cm	Length Barrel
er G	Div		18 1/4" / 46.35 cm	Length total
			8 1/4"/ 21 cm	Height
			3/8" Q.D. Socket SS	Inlet
			2.8 Lbs / 1.3 Kgs	Weight
			21250B-4000-CR	Handle
			NO	Whip hose
			NO	Whip hose SS ends
			3/8" Q.D. Plug SS	P. Hose Connectors

 Shipping Dimensions

 0625-G
 Box 25x20x10"
 10 Lbs /4.5 Kgs

Diver Gun Assembly



* Pricing and specifications subject to change without notice

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com

