

CaviBlaster 1325-G

Gasoline Engine, 13 gpm & 2,500 psi

Specifications and Options

Our most popular commercial unit, is a compact and lightweight system with superior cleaning performance utilizing the Ultra-Cavitation technology



Accessories Included:

Feed Hose (15 feet) with electric suction pump, By-Pass Hose (15 feet), High Pressure Hose (50 feet), Zero-Thrust Balanced Gun, Battery Start

Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections
Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions	
Length w/o handle	35" / 89 cm
Length w handle	45" / 114 cm
Width	26" / 66 cm
Height	29" / 74 cm
Weight	265 Lbs / 120 Kg

Pump System	
Pressure Pump	AR XWL 50.15 N
Pump Material / Type	Triplex Plunger - Brass
Flow Rate	13 gpm / 50 Lpm
Pressure	2,500 psi / 173 Bar
Hose Diam/Max Lgth	1/2" - 300 ft / 100 meters

Shipping Dimensions	
Pallet 40x48x36"	330 Lbs Gross weight

Drive System	
Engine	Kohler CH 740
Engine Type	2-cylinder air-cooled
Intake System	Naturally aspirated
Combustion System	Carburetor with digital CDI
Power Output Max	25 HP / 18.6 kW @ 3600
Clutch Type	Belt Drive
Starting System	Electric
Safety System	Low/Hot Oil Alarm Sensor

Feed System	
Feed Pump	Johnson L2200
Pump Material	Thermoplastic 12 V Sub.
Flow Rate @ Max Lift	31 gpm @ 3' / 1 m

Ideal For
Small to Mid size Boat Hulls
Piers, Pilings & Seawalls
Running gear & Out drivers
Pools & Indoor Underwater Installations

Tool Options
Zero-Thrust Balanced Gun
Double Un-Balanced Guns
Single CaviDome
ROV Lance

* Pricing and specifications subject to change without notice

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA
Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com



CAVIBLASTER™